

Mortars

CRETEREP 30

High Quality Repairing Mortar



General Properties:

- **CRETEREP 30** is two components ready mix repairing mortar, used for repairing cement substrata.
- Has maximum aggregate size 0.3 mm.
- Comp. (A) is a liquid & Comp. (B) is a powder.
- Is formulated to give high workability when using it as a fine paste material.
- Can be applied to the vertical, inclined & soffits surfaces.
- Has high water retention. To give excellent workability .

Uses:

- Cosmetic repair to cement substrata.
- As paste mortar prior to paints especially in facades & external finishing.
- **CRETEREP 30** is the ideal putty prior to the epoxy paint.

Application:

1. Clean substrate before application & remove all loose particles.
2. Substrate should be wet before application.
3. Mix comp. A (liquid) well in a container before use & pour in a wide vessel.
4. Add comp. B (powder) to the liquid & mix the mortar.
5. Apply **CRETEREP 30** with a suitable tool.
6. Clean tools immediately after application using water.

Technical Data:

Binder	: Hydraulic & synthetic resins.
Water Retention	: High.
Constancy Volume	: Constant DIN 1164.
Sagging	: Non-sag mortar.
Density	: 1.80 gm / cm ³ .
First Setting	: 45 min at 25°C .
Dilution	: Water, if necessary .
Admixture	: ASTM C 494-71.
Shelf Life	: 12 months in closed containers away from direct sun light, heat and humidity.

Environment:

- **CRETEREP 30** is non toxic and suitable for potable water structures .
- Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS) .

END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt

Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986

Web site : www.yasmomiser.com E-mail: yasmo@yasmomiser.com