

Mortars

# TILEGROUT

## Super Tile Grout Mortar



### General Properties:

- **TILEGROUT** is a ready mix cement base dry powder for tile grouting; just add water.
- Formulated to fill tile joints with high workability & excellent adhesion.
- Does not fluctuate up during application.
- Has high weather resistance & washability.
- The first setting time is about 2 hours.

### Uses:

It is used to fill joints between tiles, ceramic, marble, granite, mosaic with thickness 2-4 mm .

### Application:

1. Clean joints & remove any extra adhesive at edges.
2. Damp the joints with water.
3. Put water in vessel & add **TILEGROUT** (powder) & mix well.
4. After 5 minutes repeat mixing.
5. Apply **TILEGROUT** using a rubber edged spatula to fill the joints.
6. **Note:** Porous tiles should be protected before applying **TILE GROUT**.
7. Using a wet sponge clean tile from extra **TILEGROUT**.
8. Polish the tiles using a clean dry cloth.
9. Clean tools immediately after application.

### Technical Data:

<b>Pot life</b>	: 2 hours at 25°C
<b>Shrinkage</b>	: Nil
<b>Density</b>	: 1.8 kg/lit after setting
<b>Pulloff Strength</b>	: On concrete average 9.0 Kg / cm <sup>2</sup>
<b>Color</b>	: White or colored.
<b>Consumption</b>	: depend on the volume of the joints
<b>Shelf Life</b>	: 12 months in closed container and away from sunlight, heat and humidity.

### Environment:

- **Tile Grout** is non toxic, thus suitable for potable water structures.
- Boots, rubber gloves, dust masks, and safety goggles.
- Refer to SAFETY MATERIAL DATA SHEETS (MSDS).

END OF TECHNICAL DATA

**For more information please contact our technical department**

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt

Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986

Web site : [www.yasmomISR.com](http://www.yasmomISR.com) E-mail: [yasmo@yasmomISR.com](mailto:yasmo@yasmomISR.com)