

Finishing

# GRANULIC

## Colored Decorative Coat



### General Properties:

- **GRANULIC** is ready mix decorative colored paste, pigmented with special high standard colors.
- Combined with blended aggregates to provide a decorative shaded coat.
- Non-sag plaster coat.
- Easy for application.
- Excellent adhesion to cement substrata.
- High resistance to ultra violet.
- Consists of natural blended aggregates.

### Uses:

- Facades.
- Staircases.
- Decorative uses.

### Application:

1. Clean surface; be sure it is free from all foreign materials.
2. Any cracks or scratches should be repaired before application (recommended **CRETREP**)

**Note:** The temperature of substrate should not exceed 30°C during application & it is recommended to damp the surface using water, especially in summer.

3. Mix the **GRANULIC** well in the container before application.
4. **GRANULIC** can be thinned with water if necessary.
5. Using a stainless Steel trowel apply **GRANULIC** to substrate.
6. Average thickness approximately 2mm - 3mm depending on the roughness of the surface.
7. Clean tools using water directly after application.

### Technical Data:

<b>Binder</b>	: Synthetic resins
<b>Anti Fungus</b>	: Fungicide
<b>U.V. Resistance</b>	: Non-yellowing
<b>Dilution</b>	: Water if necessary
<b>Consumption</b>	: 3 – 4 kg / m <sup>2</sup>
<b>Environmental</b>	: friendly
<b>Packaging</b>	: 20 kg
<b>Shelf Life</b>	: 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
  - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DATA

**For more information please contact our technical department**

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt  
 Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986  
 Web site : [www.yasmomiser.com](http://www.yasmomiser.com) E-mail: [yasmo@yasmomiser.com](mailto:yasmo@yasmomiser.com)



28437/A

28437/B

28437/C