

Finishing

GRANULITE

Decorative Coat



General Properties:

- **GRANULITE** is a ready mix paste mortar, ready to be applied directly from the container.
- The filling consists of natural blended colored stones.
- Gives the effect of natural color, which will not be affected by ultraviolet.
- Non-sag mortar.
- Easy for application.
- Excellent adhesion to substrate.
- Excellent wash ability.

Uses:

- External facades.
- Staircases.
- Decorative uses.

Application:

1. Ensure that substrate is clean & free from foreign materials.
2. All cracks & scratches should be repaired before application (Recommended **CRETREP**).
Note: The temperature of substrate during application should be less than 30°C & it is recommended to damp the surface before application especially in summer.
3. Mix the material well in the container, before application.
4. **GRANULITE** can be thinned with water if necessary.
5. Apply **GRANULITE** using stainless steel trowel.
6. Average thickness is approximately 2mm - 3mm & depends on surface leveling.

Technical Data:

Binder	: Synthetic resins
Anti Fungus	: Fungicide
U.V. Resistance	: Non-yellowing
Density	: 1.6 kg / liter
Dilution	: Water if necessary
Consumption	: 3 – 4 kg/m ²
Environment	: Friendly
Packaging	: 20 kg
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
 Web site : www.yasmomISR.com E-mail: yasmo@yasmomISR.com



28437/A

28437/B

28437/C