

Finishing

GRIFMENT

Decorative Plaster Coat



General Properties:

- **GRIFMENT** is cement base, dry product, formulated to provide decorative irregular talon scratches.
- Consists of selected aggregates just add water before application.
- Excellent adhesion.
- Excellent washability.
- Non-sag mortar.
- Characterized by its hardness & durability.
- Suitable pot life after mixing.
- Can be supplied with different colors.

Uses:

- Facades.
- Staircases.
- Decorative internal or external purposes.
- **GRIFMENT** can be applied on all kinds of plaster, cement, stone and brick works.

Application:

1. Clean substrate & remove loose aggregates or foreign materials.
2. Wet the substrate well directly before application.
3. Put water in a suitable container (about 15% of the weight of the **GRIFMENT**) then add **GRIFMENT** powder with continuous mixing.
4. Using stainless steel trowel apply the **GRIFMENT** to the surface with a thickness according to the size of aggregates present in **GRIFMENT**.
5. Press gently using the trowel vertically, horizontally or circular to obtain the required texture.
6. Clean tools immediately after application using water.

Note: The temperature of substrate should not exceed 30°C during application & it is recommended to damp the surface using water, especially in summer

Technical Data:

Binder	: Hydraulic binder
State	: Dry powder
Consumption	: 1.8 kg / m ² / 1 mm thickness
Pot Life	: 45 minutes after mixing
Adhesion Strength	: > 1 N / mm ² on cement substrate (Din18555/6) (EN 1348)
Abrasion	: 120 mg (1000 cycle – 1000 gm)
Environment	: friendly
Packaging	: 20 kg
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
 Web site : www.yasmomiser.com E-mail: yasmo@yasmomiser.com



28437/A

28437/B

28437/C

Finishing

GRIFMENT
Decorative Plaster Coat



END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
Web site : www.yasmomISR.com E-mail: yasmo@yasmomISR.com



28437/A

28437/B

28437/C