

Finishing

MARMAR
Marble Putty**General Properties:**

- **MARMAR** is a white ready to use putty, can be colored as required to give the natural marble effect.
- Can be used on cement . gypsum and wooden surfaces with **Fillcoat super** putty as a preparation surface.
- Can be used for interior surfaces.
- Non sag during application.
- Has a good adhesion on **Fillcoat super** surface.
- Has a very high gloss as natural marble.
- Soft touch as a natural marble.

Uses:

- Finishing columns, walls and all interior parts.
- Finishing for building and entrances.
- All decorative purposes.

Application:

1. Ensure that substrate is clean, free from any foreign materials, grease, and oil.
2. Repair the surface using **Fillcoat super**
3. Sand to assure no roughness in the surface.
4. Apply **MARMAR** putty with the desired shape and color, take care to apply a minimum thickness to ensure complete dryness of the film.
5. Polish the surface using the putty knife right after application.
6. Wash the tools with water right after finishing application .

Technical Data:

Binder	: Synthetic resins.
Resistance to fungi	: fungicide.
Dilution	: Water, if necessary.
Color	: White. (Can be colored)
Consumption	: 6 – 7 m ² / 1kgm
Environment	: friendly.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
Web site : www.yasmomisr.com E-mail: yasmo@yasmomisr.com