

Finishing

MISRMIX

Decorative Dry Mix



General Properties:

- MISRMIX is cement base, dry mix mortar formulated for external & internal finishing.
- Supplied in different special colors.
- Easy for application.
- Provides saving of cost & time.
- High labor productivity.
- Excellent **cohesion & adhesion**.
- Gives high desirable textures.
- The product has relative specifications compatible to cement substrate.

Application:

1. Clean the surface from loose particle, oil, grease, or any foreign materials.
2. Surface should be wetted before applying MISRMIX.
3. Repair all cracks before application using **Creterep 30**.
4. Put the water (6 liters / 20 kg powder) in a suitable container, and then add MISRMIX gradually.
5. Mix well for at least 3 min. , leave for 25 min. and repeat mixing.(mechanical mixing)
6. Mix only the quantities required for application within 45 min.
7. Apply MISRMIX with steel trowel with proper thickness, and then leave to dry (neither wetted spots nor glossy surface).
8. Spray water over MISRMIX as this can help in final finishing.
9. Rub the surface (finishing) with a sponge or wooden rough tool.

Important Notes:

- The temperature of substrate should not exceed 30C during application & it is recommended to damp the surface using water, especially in summer
- The ratio of water should be fixed for every plastic bag to maintain the homogeneity of color.
- In case of using mechanical mixer: mix with low speed for 3 min and then leave for 5 min then remix.
- In case of manual mixing: mix for 5 min then leave for 25 min and then remix for 5 min.

Technical Data:

Binder	: Hydraulic & Synthetic resins
Water Ratio	: 30% form powder (by Wight)
Consistency	: Dry mix
Consumption	: 1.5 kg / 1 mm thickness / 1m ² .
Layer Thickness	: 1.5 - 5 mm
Pot Life	: 45 minutes after mixing
Adhesion Strength	: > 1 N / mm ² on cement substrate (Din18555/6) (EN 1348)
Abrasion	: 120 mg (1000 cycle – 1000 gm weight).
Washability	: Highly washable
Packaging	: 20 kg
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
 Web site : www.yasmomizr.com E-mail: yasmo@yasmomizr.com



28437/A

28437/B

28437/C