

Finishing

RUBCOAT

Decorative Elastic Paint



General Properties:

- **RUBCOAT** is a decorative elastic coat, its thickness can reach up to 3 mm by applying several coats.
- Gives different textures according to the used roller.
- Easy in application. One coat could be enough.
- High elasticity.
- Very easy to clean.
- Has the power of echo absorption.
- Excellent washability.
- Has high cohesion and adhesion.
- Has a matt aspect, with vertical or circular scratches depending on the application process.

Uses:

- Echo absorption coating.
- Decorative uses, hospitals, corridors, halls, theaters & cinemas.
- Works as proofing membrane to wood inclined roof systems.
- In courts, with thickness 2-3 mms as a finish coat over sound substrate. It can be reinforced with fiberglass sheets.

Application:

1. Clean the surface well & fill gaps, recommended **CRETTEREP**.
2. Primer is essential, recommended **VERSASEAL**.
3. **RUBCOAT** can be applied without pasting the surface.
4. Mix **RUBCOAT** well in container before application.
5. **RUBCOAT** can be thinned using water if necessary.
6. Using a roller apply several coats to get the required thickness.
7. First setting needs 24 hours / coat (depends on the layer thickness).
8. Clean tools immediately after application using water.

Note:

- The temperature of substrate should not exceed 30°C during application & it is recommended to damp the surface using water, especially in summer
- **RUBCOAT** can be modified to be fungicide & biocide according to client's requirement. The brand name of the product is (**RUBCOAT F**)

Technical Data:

| | |
|-----------------------|--|
| Binder | : Synthetic resins |
| Density | : 1.5 Kg/liter |
| U.V Resistance | : Non-yellowing |
| Anti Fungus | : Fungicide |
| Elongation | : 80 % |
| Dilution | : Water if necessary |
| Consumption | : 1 kg covers 2-3 m ² one coat |
| Environment | : Friendly |
| Packaging | : 5 Kg & 20 Kg |
| Shelf Life | : 12 months in closed container and away from sunlight, heat and humidity. |

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
 Web site : www.yasmomiser.com E-mail: yasmo@yasmomiser.com



28437/A

28437/B

28437/C