

Finishing

RUBTEX

Elastomeric Paint



General Properties:

- **RUBTEX** is an elastic emulsion paint based on special polymer.
- High elongation.
- Excellent scrub resistance.
- High durability.
- Excellent resistance to alkaline and water.
- Can be applied over old paints.

Uses:

- Exterior and interior paint.
- Sealer for concrete to prevent carbonation and corrosion.
- Due to its high elongation the paint can resist hair cracks that can happen in substrate.

Application:

1. Clean the substrate from dust and remove loose particles.
2. Damp the substrate with water.
3. Using a roller apply the primer coat using **VERSASEAL**.
4. Paste & level the substrate if required using **RUBFILL** paste.
5. The second day, stir the **RUBTEX** in the container before using and apply the first coat of **RUBTEX** using a roller or a brush.
6. The next day apply the second coat of **RUBTEX**.
7. The third coat can be applied by the same way, if required.
8. Clean tools using water just after application.

Note:

- The temperature of substrate should not exceed 30°C during application & it is recommended to damp the surface using water, especially in summer
- **RUBTEX** can be modified to be fungicide & biocide according to client's requirement. The brand name of the product is (**RUBTEX F**)

Technical Data:

Resin	: Synthetic resins
Elongation	: 90 % at 28°C after seven days
Brushability	: 4000 cycle after seven days
Density	: 1.39 kg / liter
U.V Resistance	: non-yellowing
Dilution	: Water if required
Environment	: Friendly
Consumption	: 6 m ² / kg for 100 microns thickness
Packaging	: 5 Kg & 15 Kg
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment:

- Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
 Web site : www.yasmomISR.com E-mail: yasmo@yasmomISR.com



28437/A

28437/B

28437/C